

Operation mode:

The MEK upper assembly (1) is mounted on the MGW or SWS upper assembly. The MEK lower assembly (2) fits onto the MGW or SWS lower assembly. The MEK is automatically coupled by the mechanical connection of the change system.


Advantages:

Mechanical, pneumatic and electric connections are established simultaneously.

Can withstand 50,000 alternating cycles

Individual wiring


Coding of the interchangeable parts



Technical specifications		MEK160-4G3/8-E
Suitable for		MGW160, SWS160
Pneumatic ducts	number P	4
	nominal width NW [mm]	G3/8
	operating pressure p [bar]	-1 to 8
Electrical ducts	no. of poles E	1 x 12
	rated current per pole I [A]	9
	rated voltage U [V]	63
	contact resistance per pole R [mΩ]	3
	contact durability (cycles)	50.000
Mass [kg]	upper assembly	0,35
	lower assembly	0,17
Protection class (higher requirement only on request)		IP40
Operating temperature range [°C]		-30 to +120




Pos.	Description
1	Upper assembly
2	O-Ring
3	Cylindrical pin
4	Lower assembly
6	Moulded seal
7	Insulation body / bushings
8	Insulation body / pins
9	Screwed cable gland Pg11




Multi energy coupling Ø160-4G3/8-1E12

G-MEK160-O-4G3/8-1E12	upper assembly, 4 x air, G3/8 radial, 1 x electrical plug 12 poles
G-MEK160-U-4G3/8-1E12	lower assembly, 4 x air, G3/8 radial, 1 x electrical bushing 12 poles



Products	Electrical connection	Cable variants
SEK-P / SEK-FE / MEK-R upper assembly	Electric strip, female (suitable for spring contacts)	M8-bushing, M12-plug, open end
SEK-P / SEK-FE / MEK-R lower assembly	Electric strip, male (including spring contacts)	M8-plug, M12-bushing, open end




Products	Electrical connection	Cable variants
SEK / MEK-PM upper assembly	Insulating body with pin contacts	M8-bushing, M12-plug, open end
SEK / MEK-PM lower assembly	Insulating body with socket contacts	M8-plug, M12-bushing, open end



As standard, we offer the listed products for self-soldering.
The contact assignment of the pre-assembled connections can be found in the following data sheets.

Ordering example: G-SEK100-O/U-1FE12
G-MEK063-O/U-6PM5-1E12


FEB12
Electric strip, female
12-poles (female)
Strip 2x 6 rows
Rated current per pole: 2A
Contact resistance < 20mΩ
Contact spacing: 2,54mm
Gilded
Solder connection




M8-bushing

M12-plug

M8 female




M12 Male



300-M8

300mm cable, circular connector M8-bushing



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	---
10	---
11	---
12	---

M8-bushing

8 poles (female)

Cable: drag chain suitable

According to IEC-61076-2-104

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Temperature range: -25...85°C

Cable: PUR halogen-free


included in: G-SEK100-O-1FE12-300-M8

G-MEK063-O-4PR4-1FE12-300-M8

spare part: EG-MEK-FEB12-300-M8-BW

300-M12

300mm cable, circular connector M12 plug



FEB12 female	colour	M12 male
1	white	3
2	brown	1
3	green	4
4	yellow	6
5	grey	8
6	pink	5
7	blue	2
8	red	9
9	black	7
10	violet	10
11	grey/pink	11
12	blue/red	12

M12-plug

12 poles (male)

Cable: drag chain suitable

12 x 0,14mm², Ø5,6

According to IEC-61076-2-104

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C

Cable: PUR halogen-free


included in: G-SEK100-O-1FE12-300-M12

G-MEK063-O-4PR4-1FE12-300-M12

spare part: EG-MEK-FEB12-300-M12

2000-OE

2000mm cable, open end



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	black
10	violet
11	grey-pink
12	blue-red

Open end

12 poles

Cable: drag chain suitable

Outer-Ø (D): 5,6 ± 0,2mm

Nominal voltage: ≤300V

Bending radius:

- fixed installation: >5 x D

- in motion: >10 x D

Wire cross-section: 12 x 0,14mm²

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C

Material: PUR halogen-free



Rated current (at 30°): 2 A

included in: G-SEK100-O-1FE12-2000-OE

G-MEK063-O-4PR4-1FE12-2000-OE


spare part: EG-MEK-FEB12-2000OE

FES12
Electric strip, male
Spring contacts
12 poles (male)
Strip 2x 6 rows
Spring force: 0,6N at 0,7mm
Rated current per pole: 2A
Contact resistance < 20mΩ
Contact spacing: 2,54mm
Gilded
Solder connection
Max stroke: 2,4mm



40-M8

40mm cable, circular connector M8 plug



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	---
10	---
11	---
12	---


M8 plug
8 poles (male)
Cable: drag chain suitable
Operating voltage: max 30 V
Rated current (at 30°): 1,5 A
Temperature range: -25...85°C
Cable: PUR halogen-free

included in: G-SEK100-U-1FE12-40-M8
G-MEK063-U-4PR4-1FE12-40-M8

spare part: EG-MEK-FES12-40-M8-SW

300-M12

300mm cable, circular connector M12 bushing



FES12 male	colour	M12 fem.
1	white	3
2	brown	1
3	green	4
4	yellow	6
5	grey	8
6	pink	5
7	blue	2
8	red	9
9	black	7
10	violet	10
11	grey/pink	11
12	blue/red	12


M12 bushing
12 poles (female)
Cable: drag chain suitable
12 x 0,14mm ² , Ø5,6
According to IEC-61076-2-104
Operating voltage: max 30 V
Rated current (at 30°): 1,5 A
Insulation resistance: ≥10 ³ Ω
Temperature range: -25...85°C
Cable: PUR halogen-free

included in: G-SEK100-U-1FE12-300-M12
G-MEK063-U-4PR4-1FE12-300-M12

spare part: EG-MEK-FES12-300-M12

2000-OE

2000mm cable, open end



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	black
10	violet
11	grey-pink
12	blue-red

Open end
12 poles
Cable: drag chain suitable
Outer-Ø (D): 5,6 ± 0,2mm
Nominal voltage: ≤300V
Bending radius:
- fixed installation: >5 x D
- in motion: >10 x D
Wire cross-section: 12 x 0,14mm ²
Insulation resistance: ≥10 ³ Ω
Temperature range: -25...85°C
Material: PUR halogen-free
Rated current (at 30°): 2 A

included in: G-SEK100-U-1FE12-2000-OE
G-MEK063-U-4PR4-1FE12-2000-OE
spare part: EG-MEK-FES12-2000OE


IKS12

Insulating body with pins

12 poles (male)

Rated current per pole: 9A



Contact resistance < 3mΩ



M8 bushing


M12 plug

M8 female


M12
Male


300-M8

300mm cable, circular connector M8 bushing



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	---
10	---
11	---
12	---

M8 bushing

8 poles (female)

Cable: drag chain suitable

According to IEC-61076-2-104

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Temperature range: -25...85°C

Cable: PUR halogen-free


included in: G-SEK100-O-1E12-300-M8

G-MEK063-O-6PM5-1E12-300-M8

spare part: EG-MEK-IKS12-300-M8-BW

300-M12

300mm cable, circular connector M12 plug



pin assignment	
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey-pink
12	blue-red

M12 plug

12 poles (male)

Cable: drag chain suitable

12 x 0,14mm², Ø5,6

According to IEC-61076-2-104

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C

Cable: PUR halogen-free

included in: G-SEK100-O-1E12-300-M12

G-MEK063-O-6PM5-1E12-300-M12

spare part: EG-MEK-IKS12-300-M12

2000-OE

2000mm cable, open end



pin assignment	
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey-pink
12	blue-red

Open end

12 poles

Cable: drag chain suitable

Outer-Ø (D): 5,6 ± 0,2mm

Nominal voltage: ≤300V

Bending radius:

- fixed installation: >5 x D

- in motion: >10 x D

Wire cross-section: 12 x 0,14mm²

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C

Material: PUR halogen-free

Rated current (at 30°): 2 A

included in: G-SEK100-O-1E12-2000-OE

G-MEK063-O-6PM5-1E12-2000-OE

spare part: EG-MEK-IKS12-2000-OE


IKB12

Insulating body with bushings


12 poles (female)

Rated current per pole: 9A


Contact resistance < 3mΩ


M8 plug
M12 bushing


M8 male



M12 Female


40-M8

40mm cable, circular connector M8 plug



pin assignment	
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	---
10	---
11	---
12	---

M8 plug

8 poles (male)

Cable: drag chain suitable

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Temperature range: -25...85°C


Cable: PUR halogen-free

included in: G-SEK100-U-1E12-40-M8
G-MEK063-U-6PM5-1E12-40-M8

spare part: EG-MEK-IKB12-40-M8-SW

300-M12

300mm cable, circular connector M12 bushing



pin assignment	
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey-pink
12	blue-red

M12 bushing

12 poles (female)

Cable: drag chain suitable

12 x 0,14mm², Ø5,6

According to IEC-61076-2-104

Operating voltage: max 30 V

Rated current (at 30°): 1,5 A

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C


Cable: PUR halogen-free

included in: G-SEK100-U-1E12-300-M12
G-MEK063-U-6PM5-1E12-300-M12

spare part: EG-MEK-IKB12-300-M12

2000-OE

2000mm cable, open end



pin assignment	
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey-pink
12	blue-red

Open end

12 poles

Cable: drag chain suitable

Outer-Ø (D): 5,6 ± 0,2mm

Nominal voltage: ≤300V

Bending radius:

- fixed installation: >5 x D

- in motion: >10 x D

Wire cross-section: 12 x 0,14mm²

Insulation resistance: ≥10³Ω

Temperature range: -25...85°C

Material: PUR halogen-free

Rated current (at 30°): 2 A

included in: G-SEK100-U-1E12-2000-OE
G-MEK063-U-6PM5-1E12-2000-OE

spare part: EG-MEK-IKB12-2000-OE